

# Protection Modernisation Engineering Justification Paper





T2BP-EJP-0005

Page 1 of 23

### Engineering Justification Paper Protection Modernisation

### 1 Executive Summary

This Engineering Justification paper sets out the proposed upgrade to our Protection Systems in line with modern technology, whilst maintaining compliance with Electricity Safety, Quality and Continuity Regulations (ESQCR) and STCP 27-01.

Support for these proposals exists in the form of a response by stakeholders at an engagement session that took place on the 5<sup>th</sup> of March 2019 at the Edinburgh International Conference Centre. Stakeholders required that SHE Transmission took a forward-thinking approach to the project's execution.

SHE Transmission has outlined the following deliverables for this approach;

- Complete refurbishment of bay protection at 23 sites including auxiliary tripping and supervision relays.
- Enhance 41 bays with post-event and real time monitoring in accordance with IEEE C37.118

The cost to deliver the preferred option stands at £22.00m. This cost is based on previous expenditure for similar tasks and would be delivered as an ongoing roll-out of project works throughout the RIIO-T2 period (2021 to 2026).

Upon delivery, several benefits relating to the RIIO-T2 business goals will be realised:

- Bay enhancements allow for more renewable generation to be connected to the network and contribute to the goal of "Transporting renewable electricity that powers 10 million homes" set out in the "Network for Net Zero" business plan.
- Protection enhancements from bay refurbishment reduces the likelihood of a disconnection and contributes towards the SHE-Transmission goal to aim for "100% Transmission network reliability for homes and businesses"
- Fully embraces the Digital substation concept and contributes to our goal of "£100 million in efficiency savings from innovation" outlined in the "Network for Net Zero" business plan.

This scheme is not flagged as eligible for early or late competition due to it being under Ofgem's £50m and £100m thresholds respectively.





T2BP-EJP-0005

Page 2 of 23

# Engineering Justification Paper Protection Modernisation

Name of	Protection Modernisation
Scheme/Programme	
Primary Investment Driver	Resilience
Scheme reference/	SHNLT2039
mechanism or category	
Output references/type	NLRT2SH2039
Cost	£22.00m
Delivery Year	RIIO-T2
Reporting Table	C2.25
Outputs included in RIIO	No
T1 Business Plan	



T2BP-EJP-0005

Page 3 of 23

### Engineering Justification Paper Protection Modernisation

#### 2 Introduction

This Engineering Justification Paper sets out our plans to undertake protection modernisation works during the RIIO-T2 period (April 2021 to March 2026).

The Engineering Justification Paper is structured as follows:

#### Section 3: Need

This section provides an explanation of the need for the planned works. It provides evidence of the primary and, where applicable, secondary drivers for undertaking the planned works. Where appropriate it provides background information and/or process outputs that generate or support the "need".

#### Section 4: Optioneering

This section presents all the options considered to address the "need" that is described in Section 3. Each option considered here is either discounted at this Optioneering stage with supporting reasoning provided or is taken forward for Detailed Analysis in Section 5.

#### Section 5: Detailed Analysis

This section considers in more detail each of the options taken forward from the Optioneering section. Where appropriate the results of Cost Benefit Analysis are discussed and together with supporting objective and engineering judgement contribute toward the identification of a selected option. The section continues by setting out the costs for the selected option.

### Section 6: Conclusion

This section provides summary detail of the selected option. It sets out the scope and outputs, costs and timing of investment and where applicable other key supporting information.

### Section 7: Price Control Deliverables and Ring Fencing

This section provides a view of whether the proposed scheme should be ring-fenced or subject to other funding mechanisms.

### Section 8: Outputs included in RIIO-T1 Business Plan

This section identifies if some or all the outputs were included in the RIIO-T1 Business Plan and provides explanation and justification as to why such outputs are planned to be undertaken in the RIIO-T2 period.

#### Section 9: References

Page 4 of 23



### Engineering Justification Paper Protection Modernisation

#### 3 Need

The management of legacy microprocessor-based relays continues to be a theme for RIIO-T2, much as it was in RIIO-T1. This methodology has been expanded to include the additional themes of:

- relay hardware and firmware management,
- circuit performance and
- the requirement for post-event and real time monitoring pursuant to STCP 27-01.

These themes are developed against the backdrop of the decarbonisation agenda, by ensuring that the protection offering is both compliant and agile enough to accommodate future generation connections.

### 3.1 Legacy Replacements

Our previous approach to upgrading our protection has been based around replacing time-expired assets on a "like-for-like" basis and was targeted only at principal protection relays. However, this approach did not address the associated auxiliary tripping and supervision relays. It also results in increasing fault rates towards asset end-of-life.

These assets are at an age where some platforms are obsolete or approaching obsolescence. If type faults occur, spares cannot be easily sourced, and this is likely to lead to circuit unavailability. These replacements are time consuming and can cause a business risk if not proactively managed.

### 3.2 Relay hardware/firmware management

Relays have previously been considered as "fit-and-forget" assets, only to be supported by periodic maintenance. However, microprocessor-based protection relays are subject to software and firmware "bugs" like any other electronic device, and proactive management is required to mitigate the risk of relay maloperation.

#### 3.3 Circuit Performance

Poorly performing circuits having been identified throughout RIIO-T1. Previously, generators have been teed into Major Interconnected Transmission System (MITS) circuits, with the main circuit ends left with a distance protection relay to cover the circuit. Where distance protection has been applied or historically retained due to telecommunications constraints, the relays at the circuit ends are not capable of measuring contributions from the generator and this erodes the effectiveness of the line protection.



T2BP-EJP-0005

Page 5 of 23

### Engineering Justification Paper Protection Modernisation

#### 3.4 Post-Event and Real-Time Monitoring

STC Procedure 27-01 was passed by the STC Panel in 2018, placing a set of requirements on SHE Transmission for the provision of appropriate and accurate synchronised data to monitor asset and overall system performance. Essentially this places a requirement on SHE Transmission to provide the System Operator (NGESO) with live data streams in accordance with IEEE C37.118 and suitable synchronised data to facilitate post event analysis.

The STCP requires SHE Transmission to provide devices for the measurement of said data:

- · at or near each agreed Grid Supply Point; and
- where and to the extent agreed between NGET and the relevant TO, at each point where an Interconnector or Generator is directly connected to the National Electricity Transmission System.

This will enable both post-event and real-time monitoring to understand asset performance for SHE Transmission and to facilitate dynamic/transient modelling and oscillatory stability analysis for the System Operator. The STCP mandates that the instrumentation necessary to facilitate this monitoring shall be installed throughout the RIIO-T2 time frame.

Page 6 of 23

### Engineering Justification Paper Protection Modernisation

### 4 Optioneering

When reviewing our options in this area, we produced a three-tier approach to our development in addition to a "Do Nothing" option:

#### • Minimum Requirements

 The bare minimum required to "keep the lights on" & maintain legal/regulatory compliance

### • Responsible Operator

o A more resilient network for longer term customer benefit

### • Progressive Network Enabler

 An adaptable, sustainable and flexible network providing enhanced value to current and future customers

#### 4.1 Do Nothing

This option would entail carrying out no works on protection over the course of RIIO-T2. However, it fails to address the following concerns:

- Obsolescence, with no plan to proactively address assets heading towards end-of-life,
- Bay refurbishment requirements
- Firmware management, with no proactive management to address hardware/firmware bugs,
- · Circuit performance, leaving levels of line protection at less than optimum,
- Post-fault and real-time monitoring, rendering us unable to comply with STCP 27-01.


Doing nothing would also add additional risk as primary relays would no longer be replaced.

On this basis, this option is not taken forward to detailed analysis.

#### **NOT PROGRESSED TO DETAILED ANALYSIS**

### 4.2 Minimum Requirements

The Minimum Requirements for Protection would be to replace the time expired assets on a "like-for-like" basis (insofar as is practical). Steps would have to be taken to enhance protection schemes to maintain compliance with legislation and codes. This would entail a restricted adoption of the relay





### Engineering Justification Paper Protection Modernisation

hardware / firmware management theme, abandoning the circuit performance theme and a heavily restricted adoption of the monitoring theme.

However, it fails to address the following concerns:

- · Obsolescence, with no plan to proactively address assets heading towards end-of-life,
- Bay refurbishment, continuing to focus only on primary relays; obsolete or poorly performing auxiliary relays will not be addressed
- Firmware management, with a restricted approach to addressing hardware/firmware bugs,
- Circuit Performance, leaving levels of line protection at less than optimum.
- Post-Fault and Real-time Monitoring, rendering us unable to comply with STCP 27-01.

It also fails to take account of future network risks such as reduced fault levels and system inertia, perhaps leading to regret cost arising from retro-fitting current differential protection where distance relaying is used at present.

On this basis, this option is not taken forward to detailed analysis.

### NOT PROGRESSED TO DETAILED ANALYSIS

### 4.3 Responsible Operator

In addition to the proposals under Minimum Requirements, this option includes system monitoring to meet STCP 27-01 requirements, and enhanced protection schemes able to take advantage of new telecommunications infrastructure, as well as the proactive management of relay firmware and hardware changes using enhanced data management systems. It would also provide improved circuit protection for those circuits with performance issues and an enhanced adoption of the post-event and real time monitoring theme.

This would require the modernisation of 22 feeder protection bays which have reached end-of-life. In addition to the forgoing works, an additional six circuits that previously have not had intertripping have been identified with the associated requirement for 12 intertrip panels. Plant protection replacements have been identified at three 275kV sites and thirteen 132kV sites. This work also enables compliance with STCP 27-01. More information can be found in Appendices A & B.




T2BP-EJP-0005

Page 8 of 23

### **Engineering Justification Paper Protection Modernisation**

However, this option fails to suitably protect SHE Transmission against protection relay market developments, specifically the new protocols regarding "digital substations".



T2BP-EJP-0005

Page 9 of 23

### Engineering Justification Paper Protection Modernisation

### 4.4 Progressive Network Enabler

This option expands on that outlined in Section 4.3 above through the inclusion of works required to align with IEC 61850, the international standard defining communications protocols for intelligent electronic devices at electrical substations – or "digital substations".

This would entail an enhanced adoption of the relay hardware/firmware management theme including the adoption of the digital substation in the retro-fit environment, developing circuit protection for those circuits with performance issues and an enhanced adoption of the post-event and real time monitoring theme.

This option has the additional benefit of bringing existing assets into line with the digital substation. However, by progressing to this standard, it is possible in the retro-fit environment that networking switches and such like may result in stranded assets.

In addition to the works listed under 4.3, we have identified 71 sites on our network which will require improvements to align with IEC 61850. Of these, 30 sites are addressed under our Non-Load Related Intervention portfolio so are not considered here. The remaining 41 sites contain a total of 68 bays, and the requirements consist of varying scopes of work, as shown in Table 1. Some sites require only upgraded licenses, while others need wholesale replacement of the existing protection. It is anticipated that the site end design will be such that these works can be done without need for an outage.

Category	No of	No of Bays
	sites	
Wholesale Replacement	24	41
Replacement measuring device	4	5
Measuring device requires hardware upgrade	6	12
License upgrade required	7	10

Table 1 – STCP Driven Requirements

On this basis, this option is taken forward to detailed analysis.

PROGRESSED TO DETAILED ANALYSIS

T2BP-EJP-0005

Page 10 of 23

# Engineering Justification Paper Protection Modernisation

A summary of the above optioneering is shown in Table 2, below.

	Do Nothing	Minimum Requirements	Responsible Operator	Progressive Network Enabler
Legacy	×	<b>V</b>	<b>/</b>	/
Replacements	^	•	•	•
Relay Hardware/				
Firmware	×	×	<b>✓</b>	<b>~</b>
Management				
Circuit Performance	×	×	<b>~</b>	<b>~</b>
Post Event & Real-	×	×	1	
Time Monitoring	^	^	•	•
Alignment with IEC	Y	×	×	
61850	^	^	^	•

Table 2 - Optioneering Summary



T2BP-EJP-0005

Page 11 of 23

### Engineering Justification Paper Protection Modernisation

### 5 Detailed Analysis

### 5.1 Risk and Benefit Analysis

Due to the nature of this project, risks and benefits involved are not easily quantifiable and, as agreed with Ofgem, are not suitable for traditional Cost Benefit Analysis.

In order to demonstrate the benefits of delivering this project, we have carried out a Risk and Benefit Analysis. For each option taken forward to Detailed Analysis, it looks at the existing risks, the likelihood of these risks being realised, and the severity should that happen. The likelihood and severity combine to give an overall Unmitigated Risk Rating.

Mitigation actions delivered by each option are then identified, and the likelihood and severity are reappraised, resulting in a Mitigated Risk Rating.

T2BP-EJP-0005

Page 12 of 23

### Engineering Justification Paper Protection Modernisation

This exercise was carried out for the Protection Modernisation proposals. As can be seen in the Unmitigated Risk Rating sits at "Severe". Once all the mitigations are taken into account, the Mitigated Risk Rating falls to "Medium" for both options. Both potential options derive similar amounts of improvement to the risk rating. The full Risk & Benefit Analysis is contained within Appendix C.

				Responsible Operator	Progressive Network Enabler
Risk ID	Risk Title	Risk	Unmitigated Overall Risk Rating	Mitigated Overall Risk Rating	Mitigated Overall Risk Rating
1	Age and Obsolescence	Assets are at an age where some platforms are obsolete or approaching obsolescence. If type faults occur, spares cannot be easily sourced, and this is likely to lead to circuit unavailability. These replacements are time consuming and can cause a business risk if not proactively managed	High	Medium	Medium
2	Relay Management	Relays can maloperate if software and firmware are not periodically maintained	High	Medium	Medium
3	Circuit Performance	Protection effectiveness is eroded where generators have been teed into MITS on distance protection only	Severe	Medium	Medium
4	STCP 27-01	Measurement devices required for STCP are not in place so SHE Transmission is non-compliant	Severe	Medium	Medium
5	New Technology	Technology is developing quickly and we are not in sync with modern technologies in this area. Risk is that we are left reliant on obsolete equipment	Severe	Severe	Medium
		OVERALL	Severe	Medium	Medium

Table 3 - Risk and Benefit Analysis Results

### 5.2 Stakeholder Engagement

On 5 March 2019, SHE Transmission hosted a stakeholder workshop, aimed at gathering feedback from its stakeholders on its approach to network resilience and reliability for the RIIO-T2 plan. A total of 46 stakeholders attended the workshop, representing 31 organisations.

Stakeholders supported the Progressive Network Enabler option when it was first presented to them, though it was only marginally more favoured than the Responsible Operator option. However, once costs had been discussed, the support for the Progressive Network Enabler option increased significantly. Stakeholders felt that the cost differential between the two options was negligible and the more ambitious option offered better value.

Page 13 of 23

### Engineering Justification Paper Protection Modernisation




Figure 1 - Stakeholder Feedback

There are a number of factors driving stakeholder support in this area. Stakeholders recognised that investment is required to keep up-to-date with changes in technology, that latest technologies likely offer a lower whole-life cost than their predecessors, and that digitising protection offered health and safety benefits. Stakeholders did express their concerns that this modernisation be mindful of cyber security risks and did not result in technologies being installed which become quickly obsolete.

### 5.3 Costs – Responsible Operator

These works have been estimated at £20.27m over the RIIO-T2 period. A breakdown of these costs is shown in Table 4 and requirements can be found in Appendix A.

### 5.4 Costs – Progressive Network Enabler

In total, this work is estimated at £22.00m and is required to be completed over the RIIO-T2 period, not including internal staff costs. A breakdown of these costs is shown in Table 4 and requirements can be found in Appendix A.

T2BP-EJP-0005

Page 14 of 23

### **Engineering Justification Paper Protection Modernisation**

	Responsible Operator (£M)	Progressive Network Enabler (£M)
Circuit Protection Works		
Plant Protection Works		
STCP 27-01 Works		
On Costs		
Risk & Contingency		
TOTAL		

Table 4 - Options Cost

### 5.5 Proposed Solution

We have examined each of the options in terms of three comparative factors:

- Cost
- Risk Reduction
- Stakeholder Requirements

and have determined through this analysis that the "Progressive Network Enabler" option is be preferred, as it is delivers equal risk reduction to the "Responsible Operator" option for a very small additional cost. Finally, it aligns with Stakeholder Requirements.

T2BP-EJP-0005

Page 15 of 23

### Engineering Justification Paper Protection Modernisation

#### 6 Conclusion

This Engineering Justification Paper set out the need for refurbishment of protection systems due to SHE Transmission's commitment to "Electricity Safety, Quality and Continuity Regulation 2002" (ESQCR).

SHE Transmission is required to implement STC Procedure 27-01.

The paper investigated protection modernisation of bays at key sites and determined a need that due to some assets reaching their operational life expectancy and a growing need to upgrade protection systems for future renewable generations connections.

An optioneering assessment took place which investigated 4 options, two of which were taken forward for detailed analysis.

Taking account of that detailed analysis, the preferred option is the Progressive Network Enabler option.

SHE Transmission has outlined the following deliverables for this approach;

- Complete refurbishment of bay protection at 22 sites including auxiliary tripping and supervision relays.
- Enhance 41 bays with post-event and real time monitoring in accordance with IEEE C37.118

The cost analysis for the preferred option stands at £22.00m. This cost is based on previous expenditure for similar tasks. This scheme is not flagged as eligible for early or late competition due to it being under Ofgem's £50m and £100m thresholds respectively.



T2BP-EJP-0005

Page 16 of 23

### Engineering Justification Paper Protection Modernisation

### 7 Price Control Deliverables and Ring Fencing•

As set out in our Regulatory Framework paper (section 1.12 and Appendix 3) we support a key principle from Citizens Advice – one that guarantees delivery of outcomes equivalent to the funding received - to ensure that RIIO-T2 really deliver for consumers. At the project level this means that if we don't deliver the output, or a materially equivalent outputs, we commit to returning the ex-ante allowance for the output not delivered.

This means that if the funding for Protection Modernisation should be ring-fenced and if it does not go ahead, we will return the allowances of £22.0m in full (minus any justified preconstruction expenditure).

It also means that we commit to delivering the output specified above for the costs of £22.0m. If we do not deliver the output, or a materially equivalent output, we commit to returning a proportion of the ex-ante allowance. The detailed methodology should be decided at when developing the Close Out methodologies but should apply the same principles of uncertainty mechanisms - that any under delivery should be material.



T2BP-EJP-0005

Page 17 of 23

# Engineering Justification Paper Protection Modernisation

Q	Outnuts	included in	RIIO-T1	Plans
0	Outputs	inciuaea ii	I KIIO-I I	Pialis

There are no outputs associated with this scheme included in our RIIO-T1 plans.



T2BP-EJP-0005

Page 18 of 23

# Engineering Justification Paper Protection Modernisation

### 9 References:

- Electricity Safety, Quality and Continuity Regulations 2002
- STCP 27-01 System Performance Monitoring
- IEEE C37.118



T2BP-EJP-0005

Page 19 of 23

# Engineering Justification Paper Protection Modernisation

### Appendix A – Circuit Protection Works



Table 5 - 275kV Circuit Protection Works




Table 6 - 132 kV Circuit Protection Works



T2BP-EJP-0005

Page 20 of 23

# Engineering Justification Paper Protection Modernisation

Appendix B – Plant Protection Works






Table 8 - 132kV Plant Protection Works



T2BP-EJP-0005

Page 21 of 23

### **Engineering Justification Paper Protection Modernisation**

### Appendix C – Risk & Benefit Analysis

# Scottish & Southern Electricity Networks

### Project Risk and Benefit Matrix - Responsible Operator

Risk ID	Risk Title	Risk	Unmitigated Rick Likelihood	Unmitigated Risk Impact	Unmitigated Overall Risk Rating	Mitigation Action	Mitigated Rick Likelihood	Mitigated Risk Impact	Mitigated Overall Risk Rating	Benefits
	Age and Obselesence	sasets are at an age vinere zone platforms are obsolete or approaching obsolescence. If type faults occur, parers cannot be easily sourced, and this is likely to lead to droug turnavailability. These replacements are time concurring and can cause a business talk frost proactively managed.	Likely	Serious	High	Modernisation of bays which have reached end of life	Hardly Ever	Serious	Medium	Reduces risk of lature Also provides batter value for the consumer as it makes optimal use of outages
2	Relay Management	Relays can maloperate if softs are and firms are are not periodically maintained	Possible	Serious	High	Enhanced data management systems	Hardly Ever	Serious	Medium	Proactive Management of Irmware and hardware
3	Circuit Performance	Proteotion elfectiveness is groded where generators have been teed into MITS on distance proteotion only	Likely	Major	Severe	Install intertrippping on 6 aircuits	Almost Never	Major	Medium	Improve circuit protection
4	STCP2T-DT	Measurement devices required for STCP Compliance are not in place	Almost Certain	Major	Severe	Install system monitoring devices	Almost Never	Major	Medium	SCTP Compliance; post-event and real-time monitoring
5	Nev Teahnology	Technology is developing quickly and we are not in sync with modern technologies in this area	Almost Certain	Serious	Severe		Almost Certain	Serious	Severe	

Figure 2 - Risk & Benefit Matrix – Responsible Operator

		trish & Southern tricity Networks		Proje	ct Risk ar	nd Benefit Ma	trix - Progre	essive Ne	etwork E	nabler
			Unmitigated		Unmitigated		Mitigated		Mitigated	
Risk ID	Risk Title	Hisk	Risk Likelihood	Unmitigated Risk Impact	Overall Risk Rating	Mitigation Action	Risk Likelihood	Mitigated Risk Seventy	Overall Risk Rating	Benefits
1	Ago and Obselesence	assets are at an age where some platforms are obsolete or approaching obsolessence. If type faults occur, sperse cannot be easily sourced, and this is likely to lead to circuit unavailability to the specific object of the specific object of the specific object. business its fing proactively immanged.	Likely	Serious	High	Modernisation of bays which have reached end of life	Hardly Ever	Serious	Medium	Reduces risk of fature Also provides better value for the consumer as it makes optimal use of outages
z	Relay Management	Relays can maloperate if soltware and firmware are not periodically maintained	Possible	Serious	High	Enhanced data management systems	Hardly Ever	Serious	Medium	Proactive Management of firmware and hardware
3	Crout Performance	Proteotion elfectiveness is eroded where generators have been teed into MTS or distance proteotion only	Likely	Major	Savera	Install intertrippping on 6 circuits	Alması Never	Major	Medium	improve circuit protection
4	STCP27-01	Measurement devices required for STCP Compliance are not in place	Almost Certain	Major	Severe	Install system monkoring devices	Almost Never	Major	Medium	SCTP Compliance; post-event and real-time monitoring
5	Nev Technology	Technology is developing quickly and we are not in sync with modern technologies in this area	Almost Certain	Serious	Severe	Enhanced adoption of relay hardware/frmware including	Hardly Ever	Serious	Medium	Alignment with IEC 61850

Figure 3 - Risk & Benefit Matrix – Progressive Network Enabler

T2BP-EJP-0005

Page 22 of 23

# Engineering Justification Paper Protection Modernisation

			Unm	itigate	d Likel	ihood	
		Almost Never	Hardly Ever	Unlikely	Possible	Likely	Almost Certain
Jnmitigated Impact	Catastrophic	High	High	Severe	Severe	Severe	Severe
<u>Ē</u>	Severe	Medium	High	High	Severe	Severe	Severe
ted	Major	Medium	Medium	High	High	3 Severe	evere
iga	Serious Major	Low	Medium	Medium	2) <sub>High</sub>	High	Severe
Ē	Minor	Low	Low	Medium	Medium	High	High
'n	Incidental	Low	Low	Low	Medium	Medium	Medium
			Mit	igated	Likelih	nood	
		(P		_	Likelił etwork		er)
		Almost	Mit rogress	_			er) Almost Certain
oact work	Catastrophic		rogress	ive Ne	twork	Enabl	
Impact Vetwork	Severe Catastrophic	Almost Never High Medium	rogress Hardly Ever	Unlikely	Possible	Enabl Likely	Almost Certair
ted Impact re Network	Severe	Almost Never High	Hardly Ever High High Medium	Unlikely Severe	Possible Severe	Enable Likely Severe	Almost Certain Severe
igated Impact	Serious Major Severe Catastrophic	Almost Never High Medium 3 4	Hardly Ever High	Unlikely  Severe	Possible Severe	Enable Likely Severe	Almost Certain Severe Severe
Unmitigated Impact Progressive Network	Severe	Almost Never High Medium 3 4 Medium	Hardly Ever High High Medium 1 2 5	Unlikely  Severe  High  High	Possible Severe Severe High	Enable Likely Severe Severe	Almost Certain Severe Severe

Figure 4 - Risk Heat Maps for Preferred Option