





Legend

- 10 km LVIA Study Area
- Distance from Proposed Alignment : 1 km, 2 km, 5 km
- Proposed OHL Alignment - 400 kV
- Proposed Tower - 400 kV
- Zone of Theoretical Visibility (ZTV)
(Number of Towers Visible)
- 1 - 15
16 - 30
31 - 45
46 - 60
61 - 71

ZTV Note:

- 1) The theoretical visibility is based on the design heights of the proposed towers (14.65 m – 96.57 m) of the proposed OHL alignment, including transposition towers. The assumed viewer eye height is 2 m above ground level. The visibility of these towers is cut off at 10 km each.
- 2) The digital elevation model assumes bare ground and is derived from OS Terrain 5 data. The ZTV does not take into consideration intervening vegetation and built forms. This presents a worst-case scenario.
- 3) Earth curvature and atmosphere refraction have been taken into account.
- 4) The ZTV is based on the Design Freeze 4 and does not take into account the proposed towers for the Kellas Alternative Alignment.
- 5) Refer to **Section 7.2 of Chapter 7: Landscape and Visual** for ZTV creation methodology.




Reproduced by permission of Ordnance Survey.
Crown copyright and database right 2025 all rights reserved.
Ordnance Survey Licence number AC0000813445.
SSEN Transmission take no responsibility for the release or accuracy of latest version Basemaps from Ordnance Survey

Project: Beauly to Blackhillock to New Deer to Peterhead 400 kV OHL Project


Title: Figure 7.1 - Zone of Theoretical Visibility
10 km LVIA Study Area- Bare Earth
Page 18 of 29

Drawn by: MAL Date: 12/09/2025

Drawing: B2P-WSP-DA-70092380-117




Legend



ZTV Note:

- 1) The theoretical visibility is based on the design heights of the proposed towers (14.65 m – 96.57 m) of the proposed OHL alignment, including transposition towers. The assumed viewer eye height is 2 m above ground level. The visibility of these towers is cut off at 10 km each.
- 2) The digital elevation model assumes bare ground and is derived from OS Terrain 5 data. The ZTV does not take into consideration intervening vegetation and built forms. This presents a worst-case scenario.
- 3) Earth curvature and atmosphere refraction have been taken into account.
- 4) The ZTV is based on the Design Freeze 4 and does not take into account the proposed towers for the Kellas Alternative Alignment.
- 5) Refer to **Section 7.2 of Chapter 7: Landscape and Visual** for ZTV creation methodology.




Reproduced by permission of Ordnance Survey.
Crown copyright and database right 2025 all rights reserved.
Ordnance Survey Licence number AC0000613445.
SSEN Transmission take no responsibility for the release or accuracy of latest version Basemaps from Ordnance Survey

Project: Beauly to Blackhillock to New Deer to Peterhead 400 kV OHL Project

Title: Figure 7.1 - Zone of Theoretical Visibility
10 km LVIA Study Area- Bare Earth
Page 19 of 29

Drawn by: MAL **Date:** 12/09/2025

Drawing: B2P-WSP-DA-70092380-117



Legend


- 10 km LVIA Study Area
- Distance from Proposed Alignment : 1 km, 2 km, 5 km
- Development for which Section 37 Consent is Sought
 - Proposed OHL Alignment - 400 kV
 - Temporary OHL Diversion
 - Proposed Alignment - Existing OHL Works (275 kV Realignment and Crossings)
- Proposed Tower - 400 kV
- Proposed Tower - Existing OHL Works (275 kV Realignment and Crossing)

Zone of Theoretical Visibility (ZTV) (Number of Towers Visible)



ZTV Note:

- 1) The theoretical visibility is based on the design heights of the proposed towers (14.65 m – 96.57 m) of the proposed OHL alignment, including transposition towers. The assumed viewer eye height is 2 m above ground level. The visibility of these towers is cut off at 10 km each.
- 2) The digital elevation model assumes bare ground and is derived from OS Terrain 5 data. The ZTV does not take into consideration intervening vegetation and built forms. This presents a worst-case scenario.
- 3) Earth curvature and atmosphere refraction have been taken into account.
- 4) The ZTV is based on the Design Freeze 4 and does not take into account the proposed towers for the Kellas Alternative Alignment.
- 5) Refer to **Section 7.2 of Chapter 7: Landscape and Visual** for ZTV creation methodology.



Scale: 1:2,500,000

Reproduced by permission of Ordnance Survey.
Crown copyright and database right 2025 all rights reserved.
Ordnance Survey Licence number AC0000613445.
SSEN Transmission take no responsibility for the release or accuracy of latest version Basemaps from Ordnance Survey

Project: Beauly to Blackhillock to New Deer to Peterhead 400 kV OHL Project

Title: Figure 7.1 - Zone of Theoretical Visibility
10 km LVIA Study Area- Bare Earth
Page 20 of 29

Drawn by: MAL Date: 12/09/2025

Drawing: B2P-WSP-DA-70092380-117