

Beauly to Blackhillock to New Deer to
Peterhead 400 kV Project
Environmental Impact Assessment Report
Volume 5 | Appendices

Appendix 12.1.9: Woodland Report Parcel 20200, Lovat





APPENDIX 12.1.9: Woodland Report Parcel 20200, Lovat

1	Introduction	2	
2	Woodland property		
3 Development Requirements			
	3.1 400 kV Overhead Line Infrastructure Requirements 3.2 Access Track Route Design	2	
5	4.1 Woodland Composition and Site Conditions	4	
6	Woodland Management Impact		
7	Mitigation Opportunities		
	7.1 Woodland Mitigation Measures	6	
8	Net Effect / Summary	6	
	Compensatory Planting		

Appendix Figures

Figure 12.1.9a: Parcel 20200 Location Map

Figure 12.1.9b: Parcel 20200 Proposed Felling Requirements

Figure 12.1.9c: Parcel 20200 Proposed Planting Areas



1 Introduction

- 1.1.1 This Appendix presents information relevant to the Beauly to Blackhillock to New Deer to Peterhead 400 kV Proposed Overhead Line (OHL) Project (the Proposed Development). It should be read in conjunction with the Environmental Impact Assessment (EIA) Report, specifically **Chapter 12: Forestry**, for full details of the Proposed Development.
- 1.1.2 As part of the EIA, it has been identified that construction of the OHL and the associated access tracks would cross several woodland areas within private or publicly owned landholdings.
- 1.1.3 This woodland report has been prepared to assess the potential impacts of the Proposed Development on Woodland, Parcel 20200, Lovat. It includes the requirements for woodland removal and management recommendations to mitigate the impact of the woodland removal. The report provides an overview of the characteristics of the affected woodland, including woodland composition, site conditions, soil conditions, exposure levels and existing felling approvals. The report also provides details of existing infrastructure, and potential constraints related to forestry operations. It aims to inform decision-making by identifying key environmental and logistical considerations associated with the Proposed Development. Additionally, it evaluates the feasibility of timber extraction and access whilst highlighting necessary mitigation measures to minimise disruption to the woodland ecosystem and surrounding landscape.
- 1.1.4 Field surveys of the woodland areas have been undertaken and have been used to determine the various woodland characteristics, to identify the woodland removal required and recommended. This document also sets out the area quantity hectares (ha) to be compensatory planted to ensure no net loss of woodland is achieved.

2 Woodland property

- 2.1.1 The landholding property boundaries are identified in **Figure 12.1.9a**: **Parcel 20200 Location Map**. The Lovat woodlands encompass a significant expanse within the Beauly area within the Highland Council region. The woodland is situated 1.6 km southeast of Beauly (NH 526401 443702). Forming a key component of the region's rural and ecological landscape.
- 2.1.2 The forest landscape is characterised by a mix of mature and semi-mature tree stands, interspersed with remnants of historical field boundaries that contribute to the estate's cultural and environmental heritage. While much of the woodland remains undisturbed, small sections of these historic field boundaries will be affected by the Proposed Development. Additionally, the A862 public road runs along the south of the site, serving as a key access route while also influencing land management and development considerations.

3 Development Requirements

3.1 400 kV Overhead Line Infrastructure Requirements

- 3.1.1 The Study Area for this assessment initially focussed on a 100 m width either side of the centreline of the Proposed OHL Alignment and ancillary infrastructure, where relevant, prior to the identification of an Operational Corridor (OC). The Applicant defines the OC as the area in which it has rights to remove woodland for the purposes of the safe construction, resilience and continued maintenance of OHLs, or protection of electrical plant as required by the Electricity Safety, Quality and Continuity Regulations (ESQCR) 2002¹ and The Electricity Act 1989². The OC is defined based on two different factors as follows:
 - The first factor in which the OC is determined is with reference to the distance at which a tree could fall and cause damage to the OHL, resulting in a supply outage. As a result, the OC width would be based on the

¹ UK Gov (2002). The Electricity Safety, Quality and Continuity Regulations 2002. Available at: The Electricity Safety, Quality and Continuity Regulations 2002

² UK Gov (1989). Electricity Act 1989. Available at: Electricity Act 1989



safety distance required to allow for a mature tree falling towards the OHL at the mid-point on an OHL span between two towers, taking account of topography and tree height at maturity. Standard falling distance for a mature conifer tree is considered to be a minimum of 45 m. Where the OC passes through areas of broadleaved woodland, it is noted that the width of woodland removal is likely to be reduced, due to the general lower height and characteristics of the tree species present.

- The second factor that is considered is the maximum distance that the OHL conductors can blow out from the tower under a 1 in 50-year return period wind condition, plus the required electrical clearance distance. This is to ensure that the OHL conductors do not come into contact with, or come close enough to, any object that could result in an electrical clearance infringement. This conductor blowout distance varies between each tower dependent on span length and must therefore be considered on a span-by-span basis.
- 3.1.2 The typical OC required within areas of commercial conifer forestry for a 400 kV OHL is 90 m (i.e. 45 m either side of the centre line). Where the OC passes through areas of broadleaved woodland, it is proposed that the extent of woodland removal is likely to be reduced due to the lower height of the tree species present. The OC for the Proposed OHL Alignment through areas of broadleaved woodland has been reduced to 70 m (i.e. 35 m either side of the centre line of the OHL). This has been based on the likely height of the woodland at maturity. Where any woodland removal within the OC is proposed to be reduced from the 45 m either side of the line, a site-specific assessment must be carried out to confirm that the conductor blowout does not exceed the OC width. If the conductor blowout exceeds the OC, then the width of the OC must be increased to meet the requirements of the blowout assessment as a minimum. This will ensure compliance with ESQCR requirements and that the required safety clearances are maintained.
- 3.1.3 A resilient OC of 90 m in width is required throughout the commercial conifer woodland within Woodland Parcel 13020 taking into account the requirements of the conductor blowout assessment. The OC is illustrated in **Figure 12.1.9b**: Parcel 20200 Proposed Felling Requirements.

3.2 Access Track Route Design

3.2.1 Proposed tracks in this section are found within the OC.

4 Woodland Characteristics

4.1 Woodland Composition and Site Conditions

- 4.1.1 The woodland was surveyed in November 2024. The Proposed OHL Alignment cuts through a small section of young mixed Sitka spruce (SS) plantation with a broadleaved fringe on the eastern boundary. The site was planted in 2017-18, under a Scottish Forestry Restructuring grant, Case no. 17FGS19137. This woodland is partially classed within the NatureScot Ancient Woodland Inventory as Long Established of Plantation Origin (LEPO)³, reflecting its historical use as a plantation site, but with some native woodland remnants.
- 4.1.2 The forest plantation is managed under a Long-Term Forest Plan, Case no 3782439.
- 4.1.3 The broadleaved trees, which were planted in protective tubes, are struggling to establish, primarily due to intense deer browsing.
- 4.1.4 Gorse (Ulex europaeus) and broom (Cytisus scoparius) are beginning to dominate sections of the site, potentially outcompeting young broadleaves.

³ NatureScot. A guide to understanding the Scottish Ancient Woodland Inventory (AWI). Available at: https://www.nature.scot/doc/guide-understanding-scottish-ancient-woodland-inventory-awi



- TRANSMISSION
 - The area is sheltered with a maximum Detailed Aspect Method of Scoring (DAMS) score of 10^{4,5}. Indicating some susceptibility to wind exposure but not extreme conditions.
 - The Ecological Site Classification⁶ describes the site as having a warm, sheltered and moist climate. The soils have 4.1.6 a very moist moisture status and are of medium nutrient status.
 - 4.1.7 The Soil Map of Scotland⁷ identifies the soils as being predominantly humus-iron podzols. The dominant soil type within the site consists of podzols, which are typically well-drained, nutrient-poor, and acidic.
 - 4.1.8 The proposed section of the Proposed OHL Alignment consists of a section of OC between towers BC3-2A to BC3-4A.
 - 4.1.9 The A862 is the closest forest road suitable for timber haulage within the ownership boundary. This is classed as an Agreed Route⁸ by the Timber Transport Forum⁹. Given the young age of the plantation, site conditions, and the quality of material, forestry operations in this section can be effectively carried out using a mulcher.

4.2 Photo Record – Operational Corridor Assessment

4.2.1 The following photographs provide a visual record of key locations along the OC. Each image illustrates existing vegetation types, land use, and notable landscape features relevant to the planning and management of the OC. Particular attention has been given to areas of mature woodland, natural regeneration, and locations where proposed works may intersect with ecologically or visually sensitive habitats. The photos are intended to support site assessments and inform mitigation strategies.

Photo 1: View at NH 526331 443802 looking east into the young plantation.



⁴ Forest Research (2025). Available at: http://www.forestdss.org.uk/geoforestdss/

⁵ The Detailed Aspect Method of Scoring (DAMS) is a system used to assess wind exposure in forestry and land management. It provides a numerical score that quantifies the level of exposure a site experiences based on factors such as elevation, topography, and aspect (the direction a slope faces). The DAMS score helps foresters predict wind risk, which is crucial for understanding tree stability, growth potential, and the likelihood of windthrow (trees being uprooted or broken by wind) The scoring system ranges from 0 to 24, with higher scores indicating more exposure to wind.

⁶ Ecological Site Classification, Available at: http://www.forestdss.org.uk/geoforestdss/

National Soil Map of Scotland. Available at: https://soils.environment.gov.scot/maps/soil-maps/national-soil-map-of-scotland/

⁸ Roads which can be used for timber haulage without restriction other than as regulated by the Road Traffic Act 1988. "A" roads (e.g. the A9) are classified as Agreed Routes by default unless covered by one of the other categories (e.g. Consultation Route).

⁹ The Timber Transport Forum. Introduction to Agreed Routes Map. Available at: https://timbertransportforum.org.uk/agreed-routes-map/introduction-to-agreedroutes-map/



Photo 2: View at NH 526331 443802 looking east. Showing the tubed broadleaved woodland edge.



Windblow Risk 5

- 5.1.1 It is acknowledged that the creation of the OC would result in wider potential indirect effects on the surrounding woodland areas. These areas would be subject to potential increased risk of damage (windblow). Each woodland report identifies further areas of felling to a windfirm edge, defined as 'Management Felling' (categorised as an indirect secondary impact), which is covered in more detail in the Chapter 12: Forestry in Section 12.4. Management felling would be considered as part of any application for felling permission. This would provide restocking as agreed with Scottish Forestry which would result in balancing the loss of woodland. Any felling undertaken outwith the OC would be solely under the control of the relevant landowner (and not the Applicant). It is the intention of the Applicant to encourage the landowners to follow this good practice in terms of redesign of their current Long-Term Forest Plans, which in-turn would aim to follow UK Forestry Standard (UKFS)10 for the implementation of the works required.
- 5.1.2 There is minimal risk of windblow as a result of the proposed felling, as indicated by the DAMS score and the topography of the site.
- 5.1.3 In areas where the trees are smaller due to age or exposure then the wind blow risk is reduced along with the requirement for additional felling to wind firm boundaries.

6 **Woodland Management Impact**

- 6.1.1 While tree felling within the OC will result in a slight reduction in the total area of woodland, this loss is marginal and should not significantly affect overall forest management, forest yield or access at a larger scale.
- The Proposed OHL Alignment furthermore introduces an electrical hazard, but the constraint associated with the electrical hazard will be reduced by regular maintenance of the OC which will avoid the incidences of "Red Zone" trees (reference Forest Industry Safety Accord (FISA) 804 "Electricity at Work: Forestry" 11).
- 6.1.3 The total loss of Native Broadleaved woodland resulting from the proposed alignment is 0 hectares (ha).

Scottish Forestry (2024). Available online at: https://www.forestry.gov.scot/publications/sustainable-forestry/uk-forestry-standard-ukfs
 Forest Industry Safety Accord (2020), FISA 804 Electricity at Work: Forestry. Available at: https://ukfisa.com/Safety/Safety-Guides/fisa-804



7 Mitigation Opportunities

7.1 Woodland Mitigation Measures

7.1.1 To mitigate the landscape impact on this section of the Proposed Development, a replanting strategy for areas within has been set out in **Appendix 7.6 Forestry Landscape Mitigation Principles** in the Landscape chapter will be followed where possible as demonstrated in **Figure 12.1.9c: Parcel 20200 Proposed Planting Areas**.

7.2 Restructuring

- 7.2.1 The forest within this ownership is single aged and will likely be felled all at once. Therefore, there is no positive or negative impact of the felling on the structure within the ownership.
- 7.2.2 The felling of the OC for the development, will create a new green edge, allowing the landowner to carry out future clear fell more safely in proximity to the new power line

7.3 Restocking

7.3.1 As set out in the Landscape chapter under the 'Landscape Replanting Proposals', restocking can potentially take place within the OC to mitigate the visual impact of the OC. Restocking within the OC will be carried out by the applicant. Detail shown in Figure 12.1.9c: Parcel 20200 Proposed Planting Areas.

8 Net Effect / Summary

8.1.1 **Tables 8.1 to 8.4** outline the operational requirements for forestry management within the OC between towers BC3-2A to BC3-4A. They detail the areas designated for clear felling, within the OC and forest design considerations.

Table 8.1: Woodland removal for Infrastructure, within OC

Item	Woodland Type	Area (ha)
OC felling	Young Conifer Woodland (90 m)	2.21
Total area		

Table 8.2: Compensatory Planting

Item	Woodland Type	Area (ha)
Compensatory Planting Area	Young Conifer Woodland	2.21
Total area		2.21

Table 8.3: Woodland Removal Impact of Infrastructure

ltem	Area (ha)
Total Loss of Woodland Area	2.21
Total Compensatory Planting Area	2.21
Total Net Loss of Woodland Area	



Table 8.4: Woodland removal for Management Felling, outwith OC

ltem	Woodland Type	Area (ha)
Management Felling		0.00
Replanting / Restocking Opportunities		0.00
Net Loss of Woodland Area		0.00

9 Compensatory Planting

- 9.1.1 Only areas directly impacted by the OC will be included in the compensatory planting total, in accordance with the Control of Woodland Removal Policy (CoWRP)¹². This policy ensures that woodland loss due to development is mitigated by appropriate replanting or regeneration efforts, but it specifically applies to areas where tree removal is necessary for the Proposed Development. See **Appendix 12.3 Compensatory Planting Management Strategy**.
- 9.1.2 Any additional felling outside the OC, such as areas cleared for windthrow management or forest design improvements, falls under the responsibility of the landowner and is not included in the compensatory planting requirements. Instead, these areas may be replanted under a forest plan revision or felling license at the landowner's discretion. This approach aligns with national forestry guidelines, balancing infrastructure development with sustainable woodland management.
- 9.1.3 The total amount of net felling requiring compensation under the CoWRP is 2.21 ha.
- 9.1.4 In order to provide a greater balance limiting long-term impacts on forestry interests it is proposed that the majority of this woodland loss is compensated via off-site compensatory planting within the same local authority area. It is proposed that full details of the areas subject to this off-site compensatory planting is notified to Scottish Forestry prior to energising the OHL.

 $^{{}^{12}} Forestry Commission Scotland (2009). Control of Woodland Removal Policy. Available at: \\ \underline{https://www.forestry.gov.scot/publications/285-the-scottish-government-s-policy-on-control-of-woodland-removal/viewdocument/285}$





