



BOREHOLE LOG

Beauly - Denny 400kv OHL

Borehole No
TD159B-C
Sheet 1 of 1
Status
Final
08/05/2012

Client: Scottish & Southern Energy plc
Consultant: Balfour Beatty Utility Solutions

Job No: 4578

Dale Started	04/04/2012	Initial Boring Diameter:	160mm	Coordinates:	Е	280369.722 m National Grid
Date Complete:	04/04/2012	Initial Core Diameter			N	711291.339 m National Grid
Hole Type:	RO	Rotary Casing Type	•	Ground Level:	287.	89 m OD
Equipment:	DB520	Core Barrel:		Plunge:	90°	İ
		Core Bit:		Scale:	1:50	

Description of Streta	Legend	Depth	Reduced Level		ıpling/ re Run	U	In Si	u Testing Result	TCR (SCR) ROD	FI	Install
Dark brown pseudo-fibrous PEAT with abundant small rootlets. Reddish brown slightly clayey gravelly very silty fine to medium SAND with occasional angular to sub angular cobbles of sandstone. Gravel is angular to sub rounded fine to coarse of various lithologies. Dense reddish brown slightly clayey silty gravelly fine SAND. Gravel is angular to sub rounded fine to coarse of various lithologies. (Based On Driller's Description).		1.20	287.69 286.69	D	1.50-1.95		S	46			. ,34
Weathered red SANDSTONE with very soft areas. (Driller's Description) (Open Holed).		2.70	285.19				C	50/225 50/0			
End of Borehole at 6.00 m		6.00	281.89					9)			
a Core Run		- - - - - - - - - - - - - - - - - - -	Stano	dard Per	etration Test		CP	Cable Per	cussion		

	11-4-1-4-11100 11100 0	8,	Core Run	S	Standard Penetration Test	CP	Cable Perc	ussion
U	Undisturbed U100 / U88 Sample	TCR	Total Core Recovery	C	Cone Penetration Test	RO	Rotary Ope	n Hole
1 "	Piston Sample	SCR	Solid Core Recovery	32	N for full 300mm penetration	RC	Rotary Con	ed
TW	Thin Wall Sample	RQD	Rock Quality Designation	/175	For given penetration (mm)	so	Sonic Oper	holed
D	Small Disturbed Sample	FI	Fracture Index	/25#	Seating blows only (mm)	CON		Percussion
В	Bulk Disturbed Sample	NI	Non Intact	PP	Pocket Penetrometer Test	WLS	Windowles	s Samoler
LB	Large Bulk Disturbed Sample	U"	Blows to drive U100 / U86	IPID	in-situ Photo-ionisation Detector (ppn) lostal		
w	Water Sample	UT	Thin wall undisturbed sample	L	Packer Test (Lugeons)		Slotted Pipe	Sand Filter
G	Gas Sample	NA	Not Applicable	N	Insitu Vane Test. Peak		Piezometer Tip	
c	Core	NR	No Recovery	IVR	Insitu Vane Test. Residual	₩.	•	peritorite 263)
ر ا	Amber Jar Sample	NP	No Penetration	HV	Hand Vane Test. Peak	777	Grout	Gravel Filter
v	Vial Sample	ОН	Open Hole Drilling	HVR	Hand Vane Test. Residual	(2)	Concrete	